

Data Sheet

iLED-FMB0.9-COB

Vistrol Gaia Series COB LED Fine Pitch Display Panel

The iLED-FMB0.9-COB-GA features cutting-edge COB (Chip-on Board) technology offering affordable performance for professional requirements.



Features

- **High Reliability**
Flip chip technology ensures stable and reliable performance with an extremely low failure rate.
- **Extremely Flatness**
Ultra-thin die-cast aluminum alloy cabinet design provides high precision (≤ 0.1 mm) with excellent splicing accuracy and flatness.
- **High Definition Quality**
Delivers high definition image quality with vivid and natural color reproduction.
- **Ultra High Contrast**
True contrast ratio up to 10,000:1 with better ink consistency for clearer images.
- **Super Protection**
Waterproof, dust-proof, anti-static, moisture-proof, mildew-proof, and knock-resistant design.
- **Soft Picture**
Surface light source design provides eye-friendly viewing and effectively reduces moire lines.


✓ **Technical Specifications**

LED MODULE	
Model Number	iLED-FMB0.9-COB-GA
Pixel Pitch Exhibited(mm)	0.93
Unit Plate Size(mm)	150 x 168.75
LED Type	COB(Flip Chip)
Module Size(WxH)	150 x 168.75
Pixel Per Module(dots)	160 x 180
Module Weight(kg)	0.2
Drive Type	1/60
Module Maintenance	Front
Module IP Rating (Front)	IP65
Environment	Indoor
Panel Size(mm)	600 x 337.5 x 37.7
Pixel Per Panel(dots)	640 x 360
Weight(kg/panel)	4.5
Material	Die casting aluminum
Correction	Yes, the data is stored on the module.
Brightness Uniformity	$\geq 97\%$
Chromaticity Uniformity	Within 0.003Cx,Cy
Brightness(nits)	800

R01 - V1.9

Gray Scale(bit)	14
Refresh Rate(Hz)	3840
Color Temperature(K)	3200~9300
Viewing Angle(H)	170°
Viewing Angle(V)	160°
AC Operating Voltage(V)	100~240
AC Input Frequency(Hz)	50/ 60
Power Max.(W/m2)	390
Operating Temperature (°C)	-10~+40
Operating Humidity(RH)	10%~90%
Storage Temperature(°C)	-40~+60
Storage Humidity(RH)	10%~60%
Power Double Backup	Optional
Receiving Card Dual Backup	Optional
Installation/Maintenance	Front

✓ Mechanical Drawing



Vistrol

Singapore | Malaysia

w www.vistrol.com
e sales@vistrol.com

ISO 9001:2005 Certified Company:



* For any enquiry , please send email to sales@vistrol.com

R01 - V1.9