Data Sheet

iLED-FMB1.2-COB

Vistrol Gaia Series COB LED Fine Pitch Display Panel

The iLED-FMB1.2-COB-GA features cutting-edge COB (Chip-on Board) technology offering affordable performance for professional requirements.

Features

- **High Reliability**
  The flip chip technology ensures stable and reliable performance, with an extremely low failure rate.
- **Excellent Flatness**
  Ultra thin die cast aluminum alloy shell, high precision, substrate adopts large module design.
- **Ultra Clear Picture Quality**
  Approaching the true horizon infinitely; Vividly restore natural colors.
- **Ultra High Contrast**
  The real contrast ratio is as high as 10000:1, achieving better ink consistency.
- **Soft Picture**
  Surface light source design, caring for the eyes; The product can reduce moire lines effectively.
- **Super Protection**
  Waterproof, dustproof, anti-static, moisture-proof, mildew-proof, and anti-bump for maximum durability.

√ Technical Specifications

LED MODULE	
Model Number	iLED-FMB1.2-COB-GA
Pixel Pitch Exhibited(mm)	1.25
LED Type	COB(Flip Chip)
Module Size(WxH)	150 x 168.75
Pixel Per Module(dots)	120 x 135
Panel Size(mm)	600 x 337.5 x 34
Pixel Per Panel(dots)	480 x 270
Material	Die casting Aluminum
Weight(kg/panel)	3.5
Brightness(nits)	600 ~ 800
Gray scale (bit)	14
Refresh rate (Hz)	3840
Color Temperature(K)	3200~9300
Viewing angle(H)	170°
Viewing angle(V)	160°
Power Max.(W/m^2)	330
Operating Temperature(°C)	-10~+40
Module IP Rating (Front)	IP65
Installation/Maintenance	Front

R01 - V1.9

Copyright © 2024 Vistrol. All rights reserved.